

XX-B-PR04-AC-RACK

Professional Access Control Rackmount

Data Sheet

Powerful, Space-Efficient 2-Bay 1U Rackmount Access Control Server

Achieve unmatched performance and computing with the XX-B-PRO4-AC-RACK. This 1U 2-bay rackmount access control server allows for scalable performance with the latest Intel® 8th generation Core™ processor, providing up to 30 percent more computing potential than previous generations of processors.

Two 960GB SSD (RAID 1) provide ample storage for many access control databases and other critical data. Guarantee fast response times and free up system resources with up to 16GB of DDR4 RAM.

Lower the total cost of ownership, improve system stability and maintain peace of mind with redundant, hot swappable power supplies, RAID 1 NVMe M.2 OS solid state drives, and a five-year, on-site, next business day, Keep Your Hard Drive warranty.

KEY FEATURES

- Intel[®] Core[™] i7-8700k Processor
- RAID 1 PCIe NVMe OS Solid State Drive
- Operating System: Windows 10 Pro













Back



FOR MORE INFORMATION: enexxis.com | info@enexxis.com | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.



XX-B-PR04-AC-RACK

Data Sheet

Professional Access Control Rackmount

SYSTEM	
Processor(s)	Intel® Core™ i7-8700k 8th Generation Processor (6 Cores, 12 Threads, 3.70GHz)
Processor Passmark	Intel® Core™ i7-8700k: 15,967
Operating System	Windows 10 Pro
Operating System Drives	(2) 960GB M.2 SSD
Memory	Standard Configuration: 16GB (2x 8GB)
Networking	(1) 1GbE RJ45 Ports, (1) 10GbE RJ45 Port
USB(s)	Front: (2) USB 3.1 Type A (1) USB 3.1 Type C, Rear: (2) USB 3.1 Type C
Expansion Slots	(1) Full-height PCle x16 or (2) Full-height PCle x8 slots, (1) Full-height, Half-Width PCle x4 (In default configuration)
Graphics	NVIDIA® Quadro® P400
Video Outputs	(2) USB 3.1 Type-C
Manufacturer	Enexxis
Warranty	5-Year, On-site, NBD, Keep Your Hard Drive Warranty
MECHANICAL	
Form Factor	1U Rackmount
Hard Drive Bays	(2) 3.5" Bays & (2) M.2 SSD Slots
Hard Drives Supported	PCIe NVMe, SATA
Power Supply(s)	(2) 550W (100-240VAC) 80 Plus Platinum
Maximum Power Draw	596W
Operating Temperature	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
Operating Humidity	$5 \sim 90\%$ (non-condensing)
Dimensions (WxDxH)	18.98" x 23.19" x 1.68" (482mm x 589.1mm x 42.8mm)
Max. Weight	19.27 lbs. (8.74 kg)



FOR MORE INFORMATION: enexxis.com | info@enexxis.com | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.