

Midrange and Versatile 3-Bay Tower Access Control Server

The XX-B-PRO4-AC-TWR meets the highest industry standards and can handle the 24/7 security demands of smaller-scale access control systems.

The Intel® Core™ 8th generation processor manages multiple concurrent processor-intensive tasks with capacity to spare.

Throughput optimized solid state drives (SSD) provide fast startup and application load times.

Maintain peace of mind and lower the total cost of ownership with a five-year, next business day, on-site, Keep Your Hard Drive warranty.

KEY FEATURES

- Intel® Core™ i7-8700k Processor
- PCIe NVMe OS Solid State Drive
- Operating System: Windows 10 Pro



 I/O Performance Optimized



SSD Drives



5-Year, On-site, NBD,
Keep Your Hard Drive Warranty



Intel® Core™ i7 Processor



Back

— POWERED BY —
DELL EMC

FOR MORE INFORMATION: enexxis.com | info@enexxis.com | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.

SYSTEM	
Processor(s)	Intel® Core™ i7-8700k 8th Generation Processor (6 Cores, 12 Threads, 3.70GHz)
Processor Passmark	Intel® Core™ i7-8700k: 15,963
Operating System	Windows 10 Pro
Operating System Drives	(2) 960GB SSD
Memory	Standard Configuration: 16GB (2x 8GB DDR4) (4x DDR4 DIMM Slots)
Networking	(1) 1GbE RJ45 Port
USB(s)	Rear (4) USB 3.0, (2) USB 2.0; Front (1) USB 3.0; (2) USB 2.0, (1) USB 3.1 Type-C
Expansion Slots	Standard Configuration: (1) PCIe x16 full-height, (2) PCIe x4 full-height, (1) PCI
Graphics	NVIDIA® Quadro® P400
Video Outputs	(1) DisplayPort (1) HDMI
Manufacturer	Enexxis
Warranty	5-Year, On-site, NBD, Keep Your Hard Drive Warranty
MECHANICAL	
Form Factor	Tower
Hard Drive Bays	(3) 3.5" Bays, (1) M.2 SSD Slot
Hard Drives Supported	SSD & SATA
Power Supply(s)	(1) 460W 100-240VAC
Maximum Power Draw	460W
Operating Temperature	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
Operating Humidity	5 ~ 90% (non-condensing)
Dimensions (WxDxH)	6.95" x 17.66" x 13.03" (176.6mm x 345mm x 331mm)
Max. Weight	23.37 lbs (10.6 kg)



FOR MORE INFORMATION: enexxis.com | info@enexxis.com | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.